

Amkette Analytics
Limited

Happy
New
Year



Festive
Promotion

OFFER
VALID TILL
December
2023





OUR VISION

To be the finest skills - based total solution provider for turnkey projects, delighting our customers.



OUR MISSION

The management team will focus on delivering great value to customers by developing high calibre professional skills in core competence and representing world-class instrumentation and automation products.



OUR VALUES

- ⊙ Integrity and honesty
- ⊙ Passion for customers, for our partners and technology
- ⊙ Openness and respectfulness
- ⊙ Taking on big challenges
- ⊙ Constructive self-criticism, self- improvement and personal excellence
- ⊙ Accountability towards customers, partners and employees for commitments, results and quality



OUR CORE COMPETENCIES

- ⊙ Project management
- ⊙ System integration and maintenance
- ⊙ Delivering the best solutions for MEP

INSTRUMENTS & CONSUMABLES



- Hot Air Oven
- Humidity Chamber
- Vacuum Oven



- Water Bath
- Sieve Shaker & Sieves
- Vacuum Oven
- Foamless Detergent & Neutralizer for Lab Glassware Washer/Dryer
- Universal Statistics Printer
- H2O Stabilizer



- Semi-Micro Balance
- Analytical Balance
- Precision Balance
- Electronic Top Loading Balance
- Precision Laboratory Sets



- Laboratory Viscometer
- Viscosity Standard



- Water Activity Meter



- Manual Colony Counter



- Melting Point Apparatus



- Muffle Furnace



- Refrigerators



- Autoclave



- Durachill Chillers



- BWS Series Platform Scales
- BWS Waterproof Platform Scales




- EPA/TOC Vial Kit
- HPLC UV/DAD/PDA Detector Lamps



KBF-S, KBF-S ECO Series

- ♦ Temperature range: 0 °C to +70 °C (max. 24 °C under ambient temperature) [KBF-S Eco]
- ♦ Humidity range: 10% to 80% RH [KBF-S Eco]
- ♦ Humidity regulation with capacitive humidity sensor and steam humidification
- ♦ APT.line™ preheating chamber technology
- ♦ Independent water supply via tank
- ♦ LCD to display temperature and humidity along with additional information and alarms
- ♦ Internal data logger, measured values can be read out in open format via USB






ED, FD Series

- Temperature range upto 300°C
- Electromechanical control of the exhaust air flap
- USB connection for recording data
- Controller with LCD display
- Excellent temporal and spatial temperature accuracy
- Up to 30% lower energy consumption compared to conventional units on the market
- Class 2 integrated independent adjustable temperature safety device (DIN 12880) with visual alarm
- Ergonomic handle design



Easy data logging



Completely homogeneous temperature distribution



Best energy efficiency on the market and low installation requirements



VD Series

*Vacuum pump not included in package

- Controller with digital display of pressure and temperature
- Temperature range: amb. +9°C to 220°C
- Patented expansion racks technology for optimal heat transfer
- Program-controlled drying monitoring with automatic ventilation at end of process
- Internal data logger, measured values can be read out in open format via USB
- Shatterproof, spring-mounted safety glass panel

COOLING INCUBATOR



KT Series

- Temperature range: +4 °C to +100 °C
- Class 3.1 independent temperature safety device (DIN 12880) with visual and audible temperature alarm
- APT.line™ preheating chamber technology
- Adjustable fan speed
- Electric cooling with Peltier module
- Input via pushbutton/rotary knob
- Inner door made of tempered safety glass



WB 2000V / WB 2000

- Temperature range -10°C to 100°C
- Microprocessor controlled
- Continuous operation
- External Circulation
- Can be used as chiller, circulator, water bath & refrigerated bath

Receive FREE 100 ml Trial Pack H2O Stabilizer



ADDITIVE / PRESERVATIVE FOR ALL TYPES OF WATER BATHS



Safe to use



Biodegradable



The transparency/ cleanliness of water is maintained

SIEVE SHAKER & SIEVES



SSA 200



SEV



- Intermittent and Continuous tapping motion.
- 3 directional shifting motion.
- Very low noise operation.
- Sieves made from stainless steel (Mesh- SS 316 / Ring- SS 304) with laser marking of specification & serial number
- Specially designed sieves without crevasses and without Lead
- No soldering process involved
- Lead free which makes it ideal for food grade products




Certificate

***Terms & Conditions on Back Page**



VO 100



- Dries faster than the conventional oven
- Separate vacuum release valve releasing vacuum by gentle turn of the knob
- Visual alarm for temperature deviations

Order Code	VO 100
Temperature Range	50°C to 200°C
Resolution	0.1 °C
Temperature Accuracy	± 2°C
Capacity Litres	30
Shelves	1
Rated Supply	230V, 50Hz, 15A

*Vacuum pump not included in package.


FOAMLESS DETERGENT & NEUTRALIZER FOR LAB GLASSWARE WASHER / DRYER



Order Code	Description
FLD	Foamless Detergent for Glassware Washer, 5 Ltr.
FLN	Neutralizer for Glassware Washer, 5 Ltr.

*Terms & Conditions on Back Page

**ASK FOR
SPECIAL
PRICE**



USP 100



*Universal Printer for any Weighing Balance

- ♦ Customizable modes for different applications
 - Direct Mode
 - Interval Printing
 - Statistical (Sum, Mean etc.)
 - Formulation
 - Pipette Calibration
 - Comparator Mode
- ♦ OLED Dot Matrix Display
- ♦ In-built Clock
- ♦ Password Protection for Date / Time Setting
- ♦ Plug and Play Interfacing
- ♦ Enhanced Support for ISO/GLP
- ♦ User Defined Header & Footer

PRECISION LABORATORY SETS

SHIMADZU
Excellence in Science



UPTO
38%
DISCOUNT

TX-E1-1200
TX-E2-1200



UPTO
43%
DISCOUNT

TX-F1-1200
TX-F1-1500

- ♦ Individual Weights are available on request
- ♦ Test certificate included with each set
- ♦ NABL traceable certificate available at extra cost
- ♦ Re-certification services available at extra cost
- ♦ All sets are supplied with standard accessories

Order Code	OIML Class	Description
TX-E1-1200	E1	Non-Magnetic Stainless Steel Weight Set includes 1mg-200gm, Qty 23 pcs/Set includes: mg: 1, 2, 5, 10, 20, 50, 100, 200, 500 / gm: 1, 2, 5, 10, 20, 50, 100, 200
TX-E2-1200	E2	Non-Magnetic Stainless Steel Weight Set includes 1mg-200gm, Qty 23 pcs/Set includes: mg: 1, 2, 5, 10, 20, 50, 100, 200, 500 / gm: 1, 2, 5, 10, 20, 50, 100, 200
TX-F1-1200	F1	Non-Magnetic Stainless Steel Weight Set includes 1mg-200gm, Qty 23 pcs/Set includes: mg: 1, 2, 5, 10, 20, 50, 100, 200, 500 / gm: 1, 2, 5, 10, 20, 50, 100, 200
TX-F1-1500	F1	Non-Magnetic Stainless Steel Weight Set includes 1mg-200gm, Qty 24 pcs/Set includes: mg: 1, 2, 5, 10, 20, 50, 100, 200, 500 / gm: 1, 2, 5, 10, 20, 50, 100, 200, 500

*Aluminum Carrying Case with 1 x Special Cleaning Brush, 1 x Wipe, 1 x SS Tweezer, 1 x Glove

*Terms & Conditions on Back Page

**BUY BACK
OFFER**

Promo Code


ANM-FP-AP-17
ANM-FP-AP-18
ANM-FP-AP-19
ANM-FP-AUW-20



AP-W / AP-WD



USP 100



AUW-D

- Advanced Performance UniBloc Balances
- Provides High-Speed Response and High Stability
- Response and stability settings can be changed during measurements with a single touch.

Model	Type	Calibration	Display	Capacity	Pan Size
AP135W	Super Range	Internal	0.01mg	135 g	Ø 91 mm
AP125WD	Dual Range	Internal	0.01 / 0.1 mg	52g / 120 g	Ø 91 mm
AP225WD*	Dual Range	Internal	0.01 / 0.1 mg	102g / 220g	Ø 91 mm
AUW220D	Dual Range	Internal	0.01 / 0.1 mg	82g / 220 g	Ø 80 mm

*AP225WD Promotional Offer is Valid ONLY for Non-Pharma and Non-Shimadzu HPLC Users

ANALYTICAL BALANCE

**BUY BACK
OFFER**

Promo Code

ANM-FP-AP-21
ANM-FP-AP-22
ANM-FP-AP-23
ANM-FP-AP-24

AP-X / AP-W



- 21 CFR Part 11 Compliant.
- RS-232C Interface.
- User ID and Password Management.
- Variety of Accessories and options suitable for analytical measurements.
- Minimum Measurement Value (only in AP-W Series Model).

Model	Type	Calibration	Display	Capacity	Pan Size
AP224W	Analytical	Internal	0.1mg	220 g	Ø 91 mm
AP324W	Analytical	Internal	0.1mg	320 g	Ø 91 mm
AP224X	Analytical	Internal	0.1mg	220 g	Ø 91 mm
AP324X	Analytical	Internal	0.1mg	320 g	Ø 91 mm

*Terms & Conditions on Back Page



TX-L



- ♦ Full Glass Draft Shield (3 side openable)
- ♦ Directly compatible with Windows
- ♦ UniBloc Technology

Model	Type	Calibration	Display	Capacity	Pan Size
TX323L*	Top Pan	External	1mg/0.001g	320g	Ø 110
TX423L*	Top Pan	External	1mg/0.001g	420g	Ø 110

* Limited Stock available. Promotion is subject to stock availability on first come first serve. Any of the model TX323L/ TX423L will be supplied as per stock availability.

ELECTRONIC TOP LOADING BALANCE



UP-Y

- ♦ Full Aluminum Die Cast Housing provides excellent chemical resistance.
- ♦ UP Series balances have been shown to operate with PLCs from major companies.

- ☒ High Speed ☒ Toughness
- ☒ Stress Free ☒ Efficiency & Productivity

Model	Type	Calibration	Display	Capacity	Pan Size
UP423Y	Precision	External	1mg/0.001g	420g	108x105 mm



SPECIAL

**BUY BACK
OFFER***



B-ONE PLUS

GET 2
VISCOMETERS
IN 1

LV + RV = LR

The ONLY Touch Screen Viscometer in its class to offer continuous sensing & data display.

- 7" Touch Screen Display
- Rotating Springless Technology
- Wide Speed Range upto 250rpm
- Robust Ball Bearing Suspension
- SS316 Spindles
- Direct measure with Time to Stop
- Bayonet Fitting for Quick & EZ Spindle Connection
- Units : cP, P, mPa.s, Pa.s
- Built-in USB Port for Data Transfer
- Temperature Probe included
- User & Locked mode

Model	Min. cP (mPa.s)	Max. cP (mPa.s)	RPM	No.of Speeds
B-ONE PLUS LR(Low Range LV-RV)	1*	22M	0.1-250	UNLIMITED
B-ONE PLUS HR(High Range RV, HA-5HB)	33*	370M*	0.1-250	UNLIMITED

*Minimum range can be extended to as low as 1cP (LR)/33cP (HR) with the use of MS-ULV Ultra Low Viscosity Adapter

*Maximum range can be extended to as high as 370m with use of special spindle

*Buy-Back Offer is valid for exchange with any Brand Viscometer, Working or Non-Working, Analog/Dial Type or Digital Viscometer

VISCOSITY STANDARD

Silicone Viscosity Standards provide a convenient, reliable means of checking the performance of most Viscometers / Rheometers. These fluids are calibrated at 25°C and available in 500mL bottle.



**ASK FOR
SPECIAL
PRICE**




CPS 5	CPS 5000
CPS 10	CPS 12500
CPS 50	CPS 30000
CPS 100	CPS 60000
CPS 500	CPS 100000
CPS 1000	

*Terms & Conditions on Back Page



MPA 100

- ♦ Automatic & Visual determination
- ♦ PID-controlled temperature ramping
- ♦ Digital movie of each melt
- ♦ 21 CFR part 11 (Optional)
- ♦ Conforms to Pharmacopeia & GLP
- ♦ Printer output



WATER ACTIVITY METER

novasina
The Art of Precision Measurement



LabMaster Neo aW

- ♦ Measuring range from 0.0300-1.000aW
- ♦ 21CFR11 compliant audit trail and User Management
- ♦ Full thermostatisation in the range of 0-60°C
- ♦ Automatic verification or adjustment
- ♦ Fast mode that guarantees results within 10 minutes
- ♦ Contactless salt standard identification by RFID

USED IN:



Pharma



Food



Cosmetics

*Terms & Conditions on Back Page



SCAN 50

- Improved Ergonomics
- Contrasting illumination of colonies (Protects User's eyes)
- Colony Count recognition by Light & Sound Signal
- Traceability is ensured
- Data Export by USB port, CSV files
- Touch Sensitive Surface for ease of Operation



Counting with Scan 50 is intuitive:
Count the colonies on your dish, the touch surface is doubled a sound or light signal.

AM ANM Industries

H2O STABILIZER |



Safe to use



The transparency/cleanliness of water is maintained



Biodegradable



All contact parts are protected against corrosion



Non irritating to skin at recommended concentrations



Heat-transfer efficiency is maintained

MUFFLE FURNACE

Nabertherm



UPTO
35%
DISCOUNT



L / LT

Touch Screen
Controller

- Heating from two sides by ceramic heating plates for an optimal temperature uniformity
- Ceramic heating plates with integral heating element which is safeguarded and easy to replace
- Adjustable air inlet integrated in door
- Exhaust air outlet in rear wall of furnace

REFRIGERATORS

GRAM
Innovative and functional storage

UPTO
48%
DISCOUNT



KG 210 / KG 310 / KG 410



Technical Specifications	Compact			
	KG 210	KG 310	KG 410	K 410
Temperature range	+2°C/+12°C			
Volume, gross	125 liters	218 liters	346 liters	
Volume, net	104	189	312	

*Terms & Conditions on Back Page



- Sterilization Temperature: 126°C or 135°C.
- Capacity from 25-110 liters.
- Easy-to-operate Color-touch Panel.
- Electromechanical Lid Lock System.
- 3 exhaust levels: Without, Fine, Small.
- 5 selectable modes: Agar, Solid, Dissolution, Liquid, Waste.
- Optional devices: Printer, Recorder, Floating Sensor, Forced Cooling Unit, Automatic water supply system, USB interface port.

MODE 1: LIQUID → HEATING → STERILIZATION → VARIABLE EXHAUST

Main applications: Sterilization of liquid, which can withstand high temperature and high pressure steam such as water, culture medium, reagent, reagent solution, liquid medicine, etc., and sterilization of waste using sterilization bag.

MODE 2: AGAR → HEATING → STERILIZATION → VARIABLE EXHAUST → WARMING

Main applications: Sterilization of agar medium (It is warmed at constant temperature to prevent clotting after sterilization).

MODE 3: SOLID → HEATING → STERILIZATION → FORCED EXHAUST

Main applications: Sterilization of instruments made of glass, ceramic, metal or rubber that can withstand high temperature, high pressure steam and rapid pressure reduction during exhaust.

MODE 4: DISSOLUTION → HEATING → WARMING

Main applications: Dissolution of agar medium (It is warmed at constant temperature to prevent clotting after heating).

DuraChill® Portable Recirculating Chillers are the most effortless chillers on the market. With a wide range of new and exclusive features, DuraChill® Chillers promote ease of use, minimal maintenance and environmental safety. DuraChill® has been designed for future migration to low global warming potential natural refrigerants.



USED IN:

- Plasma Thawing
- Condenser Cooling
- CT Scanning
- Bioreactors
- MRI
- Dry Ice Replacement
- PET Scanners
- Laser Cooling
- Tap Water Cooling Replacement
- Distillation
- FT-IR
- ICP
- Injection Molding
- Hydraulics Cooling
- Electron Microscopes
- GC/MS
- Reaction Vessels
- Semi Conductor
- Welder Cooling

BWS SERIES PLATFORM SCALES



- ♦ 52mm LCD, Display with white LED backlight
- ♦ Capacities : 60kg~300kg
- ♦ Housing : ABS plastic indicator
- ♦ Keyboard : 7keys (Mechanical switch)

Order No	Capacity	Readability	Class	Approx Weight	Pan Size
BWS-60KS	60 kg	5 g	II	16.4 kg	350 x 450 mm
BWS-150KS	150 kg	10 g	II	16.4 kg	350 x 450 mm
BWS-300KM	300 kg	20 g	II	18.3 kg	420 x 520 mm
BWS-300KL	300 kg	20 g	II	65.4 kg	600 x 800 mm

BWS WATERPROOF PLATFORM SCALES



- ♦ IP65 Water Proof Rating
- ♦ OIML approval from Delta (approval no.DK0199.165)
- ♦ Stainless steel housing and load cell
- ♦ 52mm LCD, Display with white backlight
- ♦ Capacities : 60kg ~300kg
- ♦ Keyboard : 7keys (Mechanical switch)
- ♦ Housing : SST

Order No	Capacity	Readability	Class	Approx Weight	Pan Size
BWS-4050-60K	60 kg	5 g	II	21 kg	400 x 500mm
BWS-4050-150K	150 kg	10 g	II	21 kg	400 x 500 mm
BWS-6550-150K	150 kg	10 g	II	27 kg	650 x 500 mm
BWS-6550-300K	300 kg	20 g	II	27 kg	650 x 500 mm



KT-40-0402



- ♦ New innovative one-piece cap designed to reduce chemical and particulate contamination during sample collection
- ♦ Cap is lined with a bonded silicone/PTFE septa which has been pre-conditioned to meet EPA standards
- ♦ Certificate of Analysis is included with Lot No.

Part No.	Description
KT-40-0402	40ml Clear Glass Screw Neck Vial with PP White Colour Screw Cap with Silicon natural / PTFE Beige BONDED Septa with Dust Protection Lid

HPLC UV/DAD/PDA DETECTOR LAMPS



FREE*
PEEK TUBING
TRAJAN



Guaranteed quality long life HPLC lamps
Deuterium 2000 Hour Lamps for HPLC UV Detection

- ♦ OEM equivalent lamps
- ♦ Guarantees and warranties match those offered by OEM

OEM	Cyberlab Part No.	Equivalent to
AGILENT	D2-AGI-VWD	1100/1200 VWD/UV D P/N G1314-60100/G1314-60101
AGILENT	D2-AGI-DAD	1100/1200 DAD/PDA P/N 5181-1530/2140-0813/2140-0820
AGILENT	D2-AGI-1260	1260/1290 P/N 5190-0917
WATERS	D2-WAT-2487	Alliance 2487 UV/VWD P/N WAS081142
WATERS	D2-WAT-2996	Alliance 2996 PDA/DAD P/N WAT052586/WAT057760
WATERS	D2-WAT-UPLC	ACQUITY UHPLC 2489/2998 P/N 201000186
SHIMADZU	D2-SHI-2010	LC-2010 P/N 228-37401-00
SHIMADZU	D2-SHI-SPD	SPD10A/VP P/N 228-34016-02
SHIMADZU	D2-SHI-UVAA	AA/UV Spectrophotometers P/N 062-65055-05
SHIMADZU	D2-SHI-NEXPROD	NEXERA (LC 2040/2040C) & Prominence I (LC2030/2030C) P/N 228-55626-01

*Get SGE - TRAJAN USA 2 meter PEEK Tubing Complimentary with each HPLC UV Detector Lamp when you order Qty 2 or more HPLC D2 Lamps

*Terms & Conditions on Back Page

SYNERGY

— TECHNO SUPPORT & SOLUTIONS LLP —

Experience The Synergy Difference!

Contact us today to explore
how we can support your lab
instrument service needs.



TERMS & CONDITIONS:

- ❖ Prices: Ex-Warehouse Umbergaon Gujarat, India
- ❖ Taxes: GST extra as applicable
- ❖ Delivery: 4-6 Weeks after receipt of PO
- ❖ Payment: 100% Advance with PO Copy
- ❖ P&F: Shipping/Delivery Charges Extra
- ❖ Festive Promotion 2023 cancels all our earlier Promotions
- ❖ Promotion is not applicable for current rate contract
- ❖ Special: PO should specify Promotion Code
- ❖ Warranty: Manufacturer/Supplier's Standard Warranty Terms are Applicable
- ❖ Validity: 31st December 2023
- ❖ Installation: Charges Extra where applicable as per Terms by Contract Service Provider

SPECIAL NOTE:

- ❖ This Promotion is Applicable for End Customers only
- ❖ Shimadzu Balances will be invoiced by Authorized SHI-AM Dealer
- ❖ Contract Services will be provided at extra cost by Synergy Services
- ❖ Promotion is valid for One time Purchase Only

*All Logos, Brand Names, Trademarks & Part Numbers used in this booklet / Promotion are property of their respective owners.



HWASHIN INSTRUMENT



Amkette Analytics Limited

ANM House,
Plot No. A-141, Road No. 23,
Wagle Industrial Area,
Thane (W) 400 604. INDIA

Tel.: 91-22 - 6614 1500, 6668 1500
Fax: 91-22 - 6668 1600
Email: info@anmalliance.com
URL: www.anmalliance.com